

FM250T





By implementing advanced magnetic flow technology, the FM250T flow meter is ideally designed to provide very accurate water flow data. It can be set up as an inline system with pipes or hoses, or it can be quickly connected directly to a water hydrant. The Hasbra swivel ring can be easily changed out to adapt to any hydrant thread type.

Portable Magnetic Flow Meter



Digital Display of Instantaneous or Totalized Flow

Features

- Battery Operated

- Swivel Coupler

- Magnetic Sensor - Unrestricted through flow

- Static and Residual Pressure Gauge

- Computer Interface

- Excel Based Software Option

(Realtime Monitoring and Recording)

Specifications

• General Weight

12.0 kg including battery pack & adaptors.

Dimensions 390 (L) x 240 (W) x 210 (H) mm. Internal Battery Pack. DC 12V @ 400 mA. Power

Corrosion resistant LM25 aluminum. Case Material -10°C ~ +50°C. (Operating) Temperature

2.5" BAT (BC,AB Thread on both ends) Adaptors

Female Hasbra Swivel on inlet Fireman Red & anodised aluminum.

• Flowmeter

Colour

Electromagnetic. Type:

Range: 30 - 3,000 lpm, up to 5,000 lpm possible.

Resolution: $0 \sim 750 \text{ l/min} \pm 15 \text{ l/min}$ 50 l/min ~ ±2%

Functions: Flow reading

Totalizer reading

Casing Material: Corrosion resistant

ADC6-12 (JIS) aluminum (anodised).

Pressure rating: 49 bar

Digital LCD gauge: Display:

4 digits

17.6mm high digits Analog bar graph Internal backlighting

• Pressure Gauge

Bourdon Tube. Type: Range: $0 \sim 10 \text{ bar, } \pm 1\%.$

(0-7, 0-15, 0-20, 0-25 bar also supplied)

Dial: Analog type, 60 mm dial.

Battery Pack

Valve regulated rechargeable lead acid. Battery Type: 2.4 Ah (10 hours continuous operation). Rated Capacity: Recharging: Mains operated recharger is supplied.

Communication Accessories

CER100M Communication Extension Reel (100 Meters)



Extends communication distance between the flow meter and the monitoring / recording laptop or computer.



included with optional FMS (Flow Monitoring Software)



RENTALS & FIELD SERVICES AVAILABLE

e-mail mail@lakewood.com

PRINTED IN CANADA FEB. 14-2008 FM250T

e-mail mail@lakewood.com

For More Information Call → Toll Free 1-888-462-9110

U.S. Corporate Headquarters 9477 Greenback Lane, #527, Folsom, CA., U.S.A. 95630 Fax [916] 988-7994 Ph. [916] 988-7970 Canadian Corporate Headquarters #112, 9704 - 39 Ave., Edmonton, AB, Can. T6E 6M7 Fax [780] 450-3867 Ph. [780] 462-9110